

General

These tappets fit 1991 and later XL model motorcycles.

Kit contents:

Qty	Description	Part No.
4	Tappets, with roller	18559-98

Installation

NOTE

A Service Manual for your motorcycle is available from your Harley-Davidson Dealer.

Read all applicable Service Manual instructions before beginning. If any procedures are not within your capabilities, or you do not have the correct tools, have your Harley-Davidson Dealer perform the installation.

To avoid accidental start-up of motorcycle, and possible personal injury, disconnect the battery cables (negative cable first) before performing any of the following procedures. If the positive cable should contact ground with the negative cable installed, the resulting sparks may cause a battery explosion resulting in personal injury.

- 1. Remove existing tappets per applicable Service Manual instructions.
- 2. Install new tappets per applicable Service Manual.



General

These tappets fit 1991 and later XL model motorcycles.

Kit contents:

Qty	Description	
4	Tappets, with roller	

Installation

NOTE

Part No.

18559-98

A Service Manual for your motorcycle is available from your Harley-Davidson Dealer.

Read all applicable Service Manual instructions before beginning. If any procedures are not within your capabilities, or you do not have the correct tools, have your Harley-Davidson Dealer perform the installation.

WARNING

To avoid accidental start-up of motorcycle, and possible personal injury, disconnect the battery cables (negative cable first) before performing any of the following procedures. If the positive cable should contact ground with the negative cable installed, the resulting sparks may cause a battery explosion resulting in personal injury.

- 1. Remove existing tappets per applicable Service Manual instructions.
- 2. Install new tappets per applicable Service Manual.