

Table of Contents

EVO: Transmission & Final Drive	3
Primary/Transmission/Final Gear Ratios	3
883 Belt Model Trans Sprocket Part Numbers	3
1200 Belt Model Trans Sprocket Part Numbers	4
Rear Belt Driven Sprocket Part Numbers	5
Final Drive Trans Belt Sprocket Issues (Differences between 1991, 1995 & 2004)	5
Belt Sizes & Part Numbers	7
Belt Twist for Carrying Spare Belt	8
Aftermarket Options	9

[Go To Technical Menu](#)

EVO: Transmission & Final Drive

Primary/Transmission/Final Gear Ratios

Evolution Engine/Trans/Final Drive - 1986-2016 - Gears & Ratios																
	Primary Drive Gears			Transmission Gear Ratios					Final Drive Gears			Overall Gear Ratios - Engine to Wheel				
	Engine	Trans	Ratio	1st	2nd	3rd	4th	5th	Trans	Wheel	Ratio	1st	2nd	3rd	4th	5th
883 Models																
1986E Chain	34T	59T	1.74	2.52	1.82	1.38	1.00	n/a	21T	48T	2.29	10.00	7.25	5.48	3.97	n/a
1986L-90 Chain	34T	59T	1.74	2.29	1.66	1.25	1.00	n/a	21T	48T	2.29	9.12	6.59	4.98	3.97	n/a
1991-92 Std/Hug Chn	35T	56T	1.60	2.773	2.022	1.485	1.215	1.000	21T	48T	2.29	10.16	7.41	5.44	4.45	3.66
1991-92 Deluxe Belt	35T	56T	1.60	2.777	2.024	1.488	1.214	1.000	27T	61T	2.26	10.04	7.32	5.38	4.39	3.61
1993-94 All Models Belt	35T	56T	1.60	2.777	2.024	1.488	1.214	1.000	27T	61T	2.26	10.04	7.32	5.38	4.39	3.61
1995-2003	35T	56T	1.60	2.685	1.969	1.433	1.178	1.000	27T	61T	2.26	9.71	7.12	5.18	4.26	3.61
2004-05	34T	57T	1.68	2.680	1.842	1.428	1.178	1.000	28T	68T	2.43	10.94	7.52	5.83	4.81	4.07
2006-10	34T	57T	1.68	2.648	1.892	1.407	1.166	1.000	28T	68T	2.43	10.78	7.70	5.73	4.75	4.07
2011+	34T	57T	1.68	2.648	1.892	1.407	1.166	1.000	29T	68T	2.35	10.41	7.44	5.53	4.58	3.93
1200 Models																
1986E 1100 Chain	34T	59T	1.74	2.52	1.82	1.38	1.00	n/a	21T	48T	2.29	10.00	7.25	5.48	3.97	n/a
1986L-87 1100 Chain	34T	59T	1.74	2.29	1.66	1.25	1.00	n/a	21T	48T	2.29	9.12	6.59	4.98	3.97	n/a
1988-90 1200 Chain	34T	59T	1.74	2.29	1.66	1.25	1.00	n/a	21T	48T	2.29	9.12	6.59	4.98	3.97	n/a
1991-94 All Models Belt	35T	56T	1.60	2.783	2.030	1.491	1.217	1.000	29T	61T	2.10	9.35	6.82	5.01	4.09	3.36
1995-2003	35T	56T	1.60	2.690	1.970	1.435	1.182	1.000	29T	61T	2.10	9.04	6.62	4.82	3.97	3.36
2004-05	38T	57T	1.50	2.688	1.848	1.433	1.180	1.000	29T	68T	2.35	9.45	6.50	5.04	4.15	3.52
2006+	38T	57T	1.50	2.648	1.892	1.407	1.166	1.000	29T	68T	2.35	9.32	6.65	4.95	4.10	3.52
1984L+ Ironheads used the same setup as the 1986E Early Evos																
1986+Ironhead Models - http://xlforum.net/vbportal/forums/showthread.php?t=513989																
1986&87 Models - http://xlforum.net/vbportal/forums/showthread.php?t=1866648																
2004+ Models - http://xlforum.net/vbportal/forums/showthread.php?t=894314																
2016-0321																

883 Belt Model Trans Sprocket Part Numbers

1991-92 883 Deluxe

1993-94E 883 All

Part	Oil Seal	Spacer	Trans Sprocket	Belt	Sprkt Kit w/mtg parts
Part #	12050	33334-85 0.849" Thick	Only-In-Kit»	40022-91 128T 1-1/8"	40285-91A 27T
As a set, the seal, spacer & sprocket from 1995 can be retrofitted back to the 1991-94 models.					

1994L-2003 883 All

Part	Oil Seal	Spacer	Trans Sprocket	Belt	Sprkt Kit w/mtg parts
Part #	12067A	33344-94 0.600" Thick	40288-95 27T	40022-91 128T 1-1/8"	40285-91B 27T

2004-06 883 All

Part	Oil Seal	Spacer	Trans Sprocket	Belt
Part #	12067B	33344-94 0.600" Thick	40379-04 28T	40570-04B 136T 1-1/8"

2007-2010 - 883

Part	Oil Seal	Spacer	Trans Sprocket	Belt
Part #	12074	Built into Bearing	40379-04 28T	40371-07 136T 1"

2011+ - 883

Part	Oil Seal	Spacer	Trans Sprocket	Belt
Part #	12074	Built into Bearing	40409-04 29T	40591-07 137T 1"

1200 Belt Model Trans Sprocket Part Numbers

1991-94E - 1200

Part	Oil Seal	Spacer	Trans Sprocket	Belt	Sprkt Kit w/mtg parts
Part #	12050	33334-85 0.849" Thick	Only-In-Kit»	40022-91 128T 1-1/8"	40202-91A 29T

As a set, the seal, spacer & sprocket from 1995 can be retrofitted back to the 1991-94 models.

1994L-03 - 1200

Part	Oil Seal	Spacer	Trans Sprocket	Belt	Sprkt Kit w/mtg parts
Part #	12067A	33344-94 0.600" Thick	40205-95 29T	40022-91 128T 1-1/8"	40202-91B 29T

2004-06 - 1200

Part	Oil Seal	Spacer	Trans Sprocket	Belt
Part #	12067B	33344-94 0.600" Thick	40409-04 29T	40571-04B 137T 1-1/8"

2007+ - 1200

Part	Oil Seal	Spacer	Trans Sprocket	Belt
Part #	12074	Built into Bearing	40409-04 29T	40591-07 137T 1"

Rear Belt Driven Sprocket Part Numbers

Rear Belt Driven Sprocket			Rear Sprocket Bolts/Washers		
Year	Part No	Part Description	Year	Part No	Description
1991-1999	40213-91	61T BLACK	1992-1999	3730A	BOLT (5)
	40227-93	61T SILVER		6516HW	WASHER (5)
2000-2003	40213-00	61T BLACK	2000-2022	3899 6516HW	BOLT (5) WASHER (5)
	40227-00	61T SILVER			
See the note below about casting# 40246-91					
2004-2006	40350-04	68T BLACK			
	40352-04	68T SILVER			
2007-2015	40350-07	68T BLACK w/highlights			
	40444-07	68T BLACK (Nightster / 883 Iron)			
	40353-08	68T BLACK (883 Iron / 48)			
2016-2022	40350-07	68T BLACK w/highlights			
	40444-07	68T BLACK (Nightster)			
	42200121	68T BLACK (48)			

NOTE: 40246-91 is a casting number - These casting numbers are on both early, 1991-1999, and late, 2000-2003, Sportster 61 tooth x 1-1/8" pulleys. The offset is the same for early and late but the early and late are not interchangeable; the early has a 2" center hole, the late is 2-3/16". There are adapters available so you can use a late (2-3/16") on an early wheel (2") , but the early does not fit the late. You can tell the late pulley visually by looking at the machined bosses for the mounting bolts. The late model bosses are intruded by the center hole and do not show completely round. The early pulleys either have no bosses or the bosses are completely round. The early pulleys are silver, the late are silver or black, from the factory.¹⁾

Final Drive Trans Belt Sprocket Issues (Differences between 1991, 1995 & 2004)

Remember, the Final Drive Trans Belt Sprocket has left-hand threads! Use a locking tool when removing or installing the sprocket.

The Final Drive Trans Belt Sprocket (from the transmission) must align with the Rear Wheel Sprocket, which is determined by the wheel width. The Trans Drive Sprocket has a belt guide flange on one side only.

For 1991-2003 the sprocket flange is away from the engine. But, there are spline differences between 1991-1994 and 1995-2003.	For 2004-later the sprocket flange is near the engine.
---	--



Pre-2004, on the outer flanged side, the center mounting splines are relatively flush with the flange face. But, on the engine side of the sprocket, the center mounting splines are recessed from the edge of the belt drive face. On 2004-later, the flange is on the engine side (with recessed splines there) and the mounting nut and lock plate are on the outer, flangeless, side.

On 1991-94 Sportsters, the flanged side of the sprocket is away from the engine. On the opposite side, between the case bearing seal (for the transmission Final Drive Shaft) and the recessed splines on the Trans Drive Sprocket, is a spacer to fit in that recess. The width of the splines in contact with the Final Drive Shaft is 0.500".

On the 1995-03 models, the center spline contact area of the Trans Drive Sprocket (on the Trans Drive Shaft) was widened to 0.766" and the recess spacer was reduced accordingly. The flanged side of the sprocket is still away from the engine. (As a set, the seal, spacer & sprocket from 1995 can be retrofitted back to the 1991-94 models.)

Note: To fit a 1995-03 pulley to a 1991-1994 model requires the matching seal. The '95+ spacer has a larger outside diameter than the 1991-94. Also note, that 1994 was a transition year to the later style pulley; "early" '94s had "early" pulley setups, "late" '94s had '95+ pulley setups.

On the 2004-later models, the Trans Drive Sprocket design was reversed. The flanged side was placed toward the engine, thereby pushing the usable belt surface farther away from the engine to allow for a wider rear tire (150mm). On the flanged side, the center mounting splines are recessed .400" from the flange face.

For 2004-2005, the older spacer (as used on '95-'03) was still used between the case bearing seal and the sprocket.

On the 2006+ models, the spacer was incorporated into the transmission output shaft bearing.

Year	Description & P/N	Note
1991-E94	Oil Seal 12050	Spacer for Sprocket with 0.500 width splines
	Spacer 33334-85	

L94-1995-2005	Oil Seal	12067B	Spacer for Sprocket with 0.766 width splines
	Spacer	33344-94	
2006-later	Oil Seal	12074	Spacer is part of shaft bearing
	Spacer	8964	

Note: The early trans pulleys will not mount to the '04-up's (even with the flange turned inboard) because:

- 1) the “extra” 1/4” for the inner spline is only a “bump”, there is no area for the nut and lockplate on the early versions.
- 2) The splines need to be recessed .400” from the (now inboard) belt flange - they are not recessed on the early versions.
- 3) With the flange outboard, the early version Final Trans Drive Sprocket cannot be properly aligned with the 2004+ Rear Wheel Sprocket. If the belt rides against the flange, overheating may occur and the flange (press fitted) can separate from the sprocket.

This [XLForum Thread](#) was used for collecting the above information. Thanks to those who contributed, especially Sirrom1.

Belt Sizes & Part Numbers

Year	PartNo	Models	Description
Chains — 530 Final Drive Chain - 530 means Pitch = 5x 1/8” & Width = 3x 1/8”			
1986-87		883/1100	106 Links
1988-90		883/1200	108 Links - 1/2” longer Swingarm
1991-92		883 Std/Hug	108 Links - 1/2” longer Swingarm
	40028-15E	883/1100/1200	Duckworth Brand 530 Chain
		Chain is 110 Links Long - Needs shortened to 106 or 108 Links 40053-65 Duckworth Connecting Link	
	40029-15E	883/1100/1200	Diamond Brand 530 Chain
		Chain is 110 Links Long - Needs shortened to 106 or 108 Links 40052-65 Diamond Connecting Link	
Year	PartNo	Models	Description
1-1/8” Belt Width			
1991-92	40022-91	883Dlx/1200	128 Tooth
1993-2003	40022-91	883/1200	128 Tooth
2004-2006	40570-04	883	136 Tooth
	40571-04B	1200	137 Tooth
1” Belt Width			
2007-2010	40371-07	883	136 Tooth
	40591-07	1200	137 Tooth
2011-2022	40591-07	883/1200	137 Tooth

Belt Twist for Carrying Spare Belt

According to Sportsterpaul (of the XLForum) it is worth carrying a spare belt for any long trip. When you replace a high mileage belt, save the old one for a spare.³⁾ Make a note of the rotation direction.

Then, carefully, do a double twist of the belt to stack it three layers high. It keeps a nice big radius (not damaging the belt) and packs well.

If your present belt should break, having a spare belt with you can work for a roadside repair, without fully removing your tire.

The suggested way to replace the belt⁴⁾ is to remove the lower bolt from the shock and swing it out of the way. Loosen the axle nut and the axle adjusters so the tire can move forward.

Slip the belt up and over the belt guard, over the front sprocket, then onto the rear sprocket from behind.

Push the tire back and readjust the adjusters & tighten the axle. Then align the shock and replace the lower bolt.



You could also shortcut the procedure (if you dare to do so carefully). Don't loosen the axle or adjusters. Just remove the lower bolt from the shock & swing it out of the way. Slip the belt up and over the belt guard, allowing it to be low behind the rear sprocket (not on it). Then slip the belt over the front sprocket & start it (as far as possible) over the rear sprocket rim at the bottom. Pull it up snug to stay in place. Then roll the bike forward so the belt pulls up around the rear sprocket and 'slips' into place. Replace the shock & bolt. The old belt will likely be a little loose from wear and will 'slip on' in this way as a 'temporary' fix until you can replace it with a new belt. Or, do it the longer way if you have any concerns.

Aftermarket Options

Various aftermarket options are listed in the REFerence Section: [HERE](#)

Go To Technical Menu

1)

Sirrom1 -

<https://www.xlforum.net/forum/sportster-motorcycle-forum/sportster-motorcycle-drivetrain/sportster-motorcycle-transmission-clutch-primary-secondary-drive/188245-rear-sprocket?t=2005973>

2)

photo by Erik

<https://www.xlforum.net/forum/sportster-motorcycle-forum/sportster-motorcycle-electrical/sportster-motorcycle-electrical-and-ignition/70015-neutral-lamp-staying-on?t=472579>

3)

<https://www.xlforum.net/showthread.php?t=14871> - Post#600

4)

<https://www.xlforum.net/forum/sportster-motorcycle-forum/sportster-motorcycle-drivetrain/sportster-motorcycle-transmission-clutch-primary-secondary-drive/46792-drive-belt-alternatives-for-emergencies?t=174407>

From:

<http://sportsterpedia.com/> - **Sportsterpedia**

Permanent link:

<http://sportsterpedia.com/doku.php/techtalk:evo:transfinal01>

Last update: **2024/08/05 21:14**

