

March 28, 2005

Owner's Manual Corrections: 2005 VRSCSE

Clock Adjustment

The 2005 VRSCSE Owner's Manual shows these instructions for setting the clock on page 41 which also shows figure 9. This has created calls since figure 9 refers to the odometer reset switch not the clock button. The instructions for setting the clock refer to figure 10 which is on page 42 and shows the location of the clock button. Below are the instructions with the correct picture. It would be a good idea to have the Sales department go over these instructions with the customer at the time of sale also.

1. Set the engine RUN/OFF switch to OFF. Turn the ignition switch ON.
2. See Figure 10. Press and hold the clock-set button for five seconds until the minutes display on the clock begins to blink. Release the button.
3. Press and release the clock-set button repeatedly to advance the minutes display. Each time you press and release the button, the display will advance one minute.
4. When the correct minute is displayed, press and hold the clock-set button for five seconds, then release. The minutes display will stop blinking, and the hours display will begin to blink.
5. Press and release the clock-set button repeatedly to advance the hours display. Each time you press and release the button, the display will advance one hour.
6. When the correct hour is displayed, press and hold the clock-set button for five seconds, then release. The hours display will stop blinking, indicating that the clock has been set.
7. Turn the ignition switch OFF.



Figure 10. Button for Setting Clock

Displacement Correction

You may also want to note that on page 20, Table 6 it states the engine displacement as 72 cu. in. This is incorrect and should read 76 cu. in.