



2007 MAINTENANCE SPECIFICATIONS

TOURING	Engine oil	3.5-4 qts.	check on side stand
	Oil Filter	63798-99A (chrome)	63731-99A (black)
	Transmission oil	32 oz (1 qt) (Check on Side Stand)	Formula Plus or Syn3
	Primary fluid	38 oz (wet) 45oz (dry)	Formula Plus or Syn3
	Tire sizes	Front: 16" D402F	Rear: 16" D402
		<i>FLHRCSE3</i> Front: 18" D418F	Rear: 17" D407 (160/70)
		<i>FLHTCUSE2</i> Front: 16" D402F	Rear: 16" D402
	Tire pressure	Front: 36 psi	Rear: 38-40 psi
		<i>FLHRCSE3</i> Front: 36-38 psi	Rear: 38-42 psi
		<i>FLHTCUSE2</i> Front: 36 psi	Rear: 38-40 psi
	Brake Fluid	DOT 4	
	Brake Pads	Front: 44082-00C	Rear: 44082-00C
	Battery #	66010-97A	
	Air cleaner #	29461-99	
Spark Plug #	32362-04	6R12	
Fork Oil	<i>FLHR/S/C</i> 11.1 oz (5.24"/133mm)		
	<i>ALL OTHERS</i> 10.8 oz (5.59"/142mm)		
SOFTAIL	Engine oil	3 qts.	check on side stand
	Oil Filter	63798-99A (chrome)	63731-99A (black)
	Transmission oil	32 oz (1 qt) (Check on Side Stand)	Formula Plus or Syn3
	Primary fluid	32 oz (1 qt)	Formula Plus or Syn3
	Tire pressure	<i>FXST/B/C</i> Front: 30 psi	Rear: 38-42 psi
		<i>FXSTD</i> Front: 30 psi	Rear: 36-40 psi
		<i>FLSTF</i> Front: 36 psi	Rear: 38-42 psi
		<i>FLSTC/F/N/CS</i> Front: 36 psi	Rear: 36-40 psi
		<i>FXSTSSE</i> Front: 30 psi	Rear: 38-42 psi
	Tire sizes	<i>FLSTNI</i> Front: 16" D402F - WW	Rear: 16" D402 - WW
		<i>FLSTC</i> Front: 16" D402F	Rear: 16" D401 (150/80)
		<i>FLSTF</i> Front : 17" D407F	Rear 17" D407 (200/55)
		<i>FX</i> Front: 21" D402F	Rear: 17" D407 (200/55)
		<i>FXSTD</i> Front: 21" D402F	Rear: 17" K591 (160/70)
		<i>FXSTSSE</i> Front : 21" D402F	Rear: 17" D407 (200/55)
	Brake Fluid	DOT 4	
	Brake Pads	Front: 44082-00C	Rear: 44082-00C
		<i>FX</i>	Rear: 46721-06
	Battery #	65989-97A	
Air cleaner #	29461-99		
Spark Plug #	32362-04	6R12	
Fork Oil	<i>FLSTC/FLSTN</i> 13.4 oz (4.41"/112mm)		
	<i>FLSTF</i> 13.4 oz (5.04"/128mm)		
	<i>FXST/FXSTB/FXSTC</i> 12.5 oz (6.69"/170mm)		
	<i>FXSTD</i> 11.6 oz (7.48"/190mm)		
DYNA	Engine oil	2.5-3 qts	check on side stand
	Oil Filter	63798-99A (chrome)	63731-99A (black)
	Transmission oil	32 oz (1 qt) (Check on Side Stand)	Formula Plus or Syn3
	Primary fluid	32 oz (1 qt)	Formula Plus or Syn3
	Tire sizes	Front: 19" D401F	Rear: 17" K591 (160/70)
		<i>FXDWG</i> Front: 21" D402F	Rear: 17" K591 (160/70)
		<i>FXDSE</i> Front: 21" D402F	Rear: 17" D407 (170/60)
	Tire pressure	Front: 30 psi	Rear: 36 psi
		<i>FXDSE</i> Front: 30 psi	Rear: 38-42 psi
	Brake Fluid	DOT 4	
	Brake Pads	Front: 44082-00C	Rear: 44082-00C
	Battery #	65989-97A	
	Air cleaner #	29461-99	
	Spark Plug #	32362-04	6R12
Fork Oil	<i>FXDWG</i> 29.6oz/875cc 4.4in/112mm		
	<i>FXD FXDL FXDC FXDB</i> 26.6oz/787cc 4.3in/110mm		



2007 MAINTENANCE SPECIFICATIONS

XL	Engine oil	3.6 qts	Check on side stand
	Oil Filter	63796-77A (chrome)	63805-80A (black)
	Transmission/ Primary oil	32 oz (1 qt)	
	Tire sizes	Front: 19" D401F Front: 21" D402F	Rear: 16" D401 (150/80)
	Tire pressure	Front: 30 psi	Rear: 36-40 psi
	Brake Fluid	DOT 4	
	Brake Pads	Front: 42831-04A	Rear: 42029-07
	Battery #	65958-04	
	Air cleaner #	29331-04	
	Spark Plug #	32362-04	6R12
	Fork Oil	883L/1200L 12.3 oz (4.80"/122mm) All Others 11.6 oz (5.75"/146mm)	
VR0D	Engine oil	5.0 qts	Check upright
	Oil Filter	63793-01K (Black)	
	Coolant	2.5 qts	
	Tire sizes	R/D Front: 19" D208F (120/70) X/DX/AW	Rear: 18" D207 (180/55) Rear: 18" D419 (240/40)
	Tire pressure	R/D Front: 36 psi X/DX/AW	Rear: 38 psi Rear: 40 psi
	Brake Fluid	DOT 4	
	Brake Pads	Front: 42897-06A (kit)	Rear: 42850-06A
	Battery #	65989-97A except VRSCR	VRSCR is 65948-00
	Air cleaner #	29437-01	
	Spark Plug #	32335-04	10R12A
	Fork Oil	VRSCR 3.15"/80mm - Left Fork VRSCAW/D/X/DX 3.58"/91mm	4.80"/122mm - Right Fork
BUELL	Engine oil	<i>XB</i> 2.5 qts <i>Blast</i> 2 qts	Check on side stand Check upright
	Oil filter #	<i>ALL</i> 63806-00Y	
	Transmission/ Primary oil	32 oz (1 qt)	Check upright-fluid level with bottom of clutch spring
	Tire sizes:	<i>XB RIS Models</i> G0150.5A8A Pirelli Diablo <i>XB9SX, XB12X Models</i> G0150.1AJ Pirelli Scorp Sync	G0350.5A8A Pirelli Diablo G0350.1AJ Pirelli Scorp Sync
	Tire pressure	<i>Blast</i> Front: G0150.T K330 16"	Rear: G0350.T K330 16"
		<i>XB</i> Front: 34 psi <i>Blast</i> Front: 28 psi \ 32 psi @ GVWR	Rear: 36 psi Rear: 30 psi \ 36 psi @ GVWR
	Brake Fluid	<i>ALL</i> DOT 4	
	Brake Pads	<i>XB</i> Front: H0300.02A8 <i>Blast</i> Front: H0300.T	Rear: H0301.T Rear: H0301.T
	Battery #	<i>ALL</i> 65948-00	
	Air cleaner #	<i>XB</i> P0213.02A8 <i>Blast</i> P0213.T	
	Spark Plug #	<i>ALL</i> 32335-04	10R12A
	Fork Oil	<i>Blast</i> 9.2 oz <i>XB9R/12R</i> 4.21" <i>XB9SX/12S/12Ss</i> 4.21" <i>XB12Scg</i> 4.29" <i>XB12X</i> 4.45"	