



2008 MAINTENANCE SPECIFICATIONS

TOURING

| | | |
|------------------|---|----------------------------|
| Engine oil | 4 qts. | check on side stand |
| Oil Filter | 63798-99A (chrome) | 63731-99A (black) |
| Transmission oil | 32 oz (1 qt) (Check on Side Stand) | Formula Plus or Syn3 |
| Primary fluid | 38 oz (wet) 45oz (dry) | Formula Plus or Syn3 |
| Tire sizes | Front: 16" D402F (130/90-16) | Rear: 16" D402 (MU90-16) |
| | <i>FLHRSE4</i> Front: 18" D407 (130/70-R18) | Rear: 17" D407 (170/60-17) |
| | <i>FLHTCUSE3</i> Front: 16" D402F (130/90-16) | Rear: 16" D402 (MU90-16) |
| Tire pressure | Front: 36 psi | Rear: 36-40 psi |
| | <i>FLHRSE4</i> Front: 36-38 psi | Rear: 38-42 psi |
| | <i>FLHTCUSE3</i> Front: 36 psi | Rear: 36-40 psi |
| Brake Fluid | DOT 4 | |
| Brake Pads | Front: 41854-08 | |
| Battery # | 66010-97B | |
| Air cleaner # | 29633-08 | |
| Spark Plug # | 32362-04 | 6R12 (Gap @ 0.040") |
| Fork Oil | <i>FLHR/C</i> 11.1 oz/328 ml 5.24in/133mm | Type E / 99884-80 |
| | <i>ALL OTHERS</i> 10.8 oz/319 ml 5.59in/142mm | Type E / 99884-80 |

SOFTAIL

| | | |
|-------------------------------|---|-------------------------|
| Engine oil | 3 qts. | check on side stand |
| Oil Filter | 63798-99A (chrome) | 63731-99A (black) |
| Transmission oil | 32 oz (1 qt) (Check on Side Stand) | Formula Plus or Syn3 |
| Primary fluid | 32 oz (1 qt) | Formula Plus or Syn3 |
| Tire pressure | <i>FXST/B/C</i> Front: 30 psi | Rear: 38-42 psi |
| | <i>FXCW/C</i> Front: 30 psi | Rear: 38-42 psi |
| | <i>FLSTF</i> Front: 36 psi | Rear: 38-42 psi |
| | <i>FLSTC/N</i> Front: 36 psi | Rear: 36-40 psi |
| | <i>FXSTSSE2</i> Front: 30 psi | Rear: 38-42 psi |
| Tire sizes | <i>FLSTN</i> Front: 16" D402F - WW | Rear: 16" D402 - WW |
| | <i>FLSTC</i> Front: 16" D402F | Rear: 16" D401 (150/80) |
| | <i>FLSTF</i> Front: 17" D407F | Rear: 17" D407 (200/55) |
| | <i>FXST</i> Front: 21" D402F | Rear: 17" D407 (200/55) |
| | <i>FXSTB/C</i> Front: 21" D407 | Rear: 17" D407 (200/55) |
| | <i>FXCW/C</i> Front: 19" D407 90/90 | Rear: 18" D407 (240/40) |
| | <i>FXSTSSE2</i> Front: 18" D407 | Rear: 17" D407 (200/55) |
| Brake Fluid | DOT 4 | |
| Brake Pads (EXCEPT FLSTSB) | Front: 44082-08 | Rear: 42298-08 |
| | <i>FLSTSB</i> Front: 44063-83C | Rear: 42298-08 |
| Battery # | 65989-97B | |
| Air cleaner # (EXCEPT FLSTSB) | 29461-99 | |
| | <i>FLSTSB</i> 29314-08 | |
| Spark Plug # | 32362-04 | 6R12 |
| Fork Oil | <i>FLSTC/FLSTN</i> 13.4 oz/395 ml 4.41in/112mm | |
| | <i>FLSTF</i> 13.4 oz/397 ml 5.04in/128mm | |
| | <i>FXST/FXSTB/FXSTC</i> 12.5 oz/370 ml 6.69in/170mm | |
| | <i>FXCW/C</i> 24.5 oz/725 ml 4.80in/122mm | |

DYNA

| | | |
|------------------|---|--------------------------|
| Engine oil | 3 qts | check on side stand |
| Oil Filter | 63798-99A (chrome) | 63731-99A (black) |
| Transmission oil | 32 oz (1 qt) (Check on Side Stand) | Formula Plus or Syn3 |
| Primary fluid | 32 oz (1 qt) | Formula Plus or Syn3 |
| Tire sizes | <i>FXD/B/C/L</i> Front: 19" D401F | Rear: 17" K591 (160/70) |
| | <i>FXDF</i> Front: 16" D427F (130/90) | Rear: 16" D427F (180/70) |
| | <i>FXDWG</i> Front: 21" D401F | Rear: 17" K591 (160/70) |
| | <i>FXDSE2</i> Front: 21" D402F | Rear: 17" D407 (170/60) |
| Tire pressure | <i>FXDF</i> Front: 36 psi | Rear: 36-40 psi |
| | <i>All except FXDF</i> 30 psi | 36-40psi |
| | <i>FXDSE2</i> Front: 30 psi | Rear: 38-42 psi |
| Brake Fluid | DOT 4 | |
| Brake Pads | Front: 44082-08 | Rear: 42298-08 |
| Battery # | 65989-97B | |
| Air cleaner # | 29191-08 | |
| Spark Plug # | 32362-04 | 6R12 |
| Fork Oil | <i>FXDWG</i> 29.6oz/875 ml 4.4in/112mm | |
| | <i>All except FXDWG</i> 26.6oz/787 ml 4.3in/110mm | |



2008 MAINTENANCE SPECIFICATIONS

| | | | |
|---------------|-----------------------------|--|-------------------------------------|
| XL | Engine oil | 2.8 qts | Check on side stand |
| | Oil Filter | 63796-77A (chrome) | 63805-80A (black) |
| | Transmission/ Primary oil | 32 oz (1 qt) | |
| | Tire sizes | <i>All except customs</i> Front: 19" D401F | Rear: 16" D401 (150/80) |
| | | <i>XL883C/XL1200C</i> Front: 21" D402F | Rear: 16" D401 (150/80) |
| | Tire pressure | Front: 30 psi | Rear: 36-40 psi |
| | Brake Fluid | DOT 4 | |
| | Brake Pads | Front: 42831-04A | Rear: 42029-07 |
| | Battery # | 65958-04 | |
| | Air cleaner # | 29331-04 | |
| | Spark Plug # | 32362-04 | 6R12 |
| | Fork Oil | <i>883L/1200L</i> 12.3 oz/364 ml 4.80in/122mm <i>All Others</i> 11.6 oz/342 ml 5.75in/146mm | |
| | VROD | Engine oil | 4.5 qts |
| Oil Filter | | 63793-01K (Black) | |
| Coolant | | 2.5 qts | |
| Tire sizes | | <i>D/DA</i> Front: 19" D208F (120/70) | Rear: 18" D207 (180/55) |
| | | <i>DX/DXA/AW/AWA</i> Front: 19" D208F (120/70) | Rear: 18" D419 (240/40) |
| Tire pressure | | <i>D/DA</i> Front: 36 psi | Rear: 38-40 psi |
| | | <i>DX/DXA/AW/AWA</i> Front: 36 psi | Rear: 38-42 psi |
| Brake Fluid | | DOT 4 | |
| Brake Pads | | Front: 42897-08 | Rear: 42850-06B |
| Battery # | | 65989-97B | |
| Air cleaner # | | 29437-01 | |
| Spark Plug # | | 32335-04 | 10R12A |
| ALL | | 3.58in/91mm | |
| BUELL | Engine oil | <i>XB</i> 2.5 qts | Check on side stand |
| | | <i>Blast</i> 2 qts | Check upright |
| | Oil filter # | 63806-00Y | |
| | Transmission/ Primary oil | 32 oz (1 qt) | Check upright |
| | Tire sizes: | <i>XB12 R</i> Front: 17" Pirelli Diablo T 120/70 | Rear: 17" Pirelli Diablo T 180/55 |
| | | <i>XB12S/Ss/Scg</i> Front: 17" Pirelli Diablo T 120/70 | Rear: 17" Pirelli Diablo T 180/55 |
| | | <i>XB9SX/XB12STT/XB12X</i> Front: 17" Pirelli Scorp Sync 120/70 | Rear: 17" Pirelli Scorp Sync 180/55 |
| | | <i>Blast</i> Front: G0150.T K330 16" 100/80 | Rear: G0350.T K330 16" 120/80 |
| | Tire pressure | <i>XB</i> Front: 34 psi | Rear: 36 psi |
| | | <i>Blast</i> Front: 28-32 psi | Rear: 30-36 psi |
| | Brake Fluid | <i>ALL</i> DOT 4 | |
| | Brake Pads | <i>XB</i> Front: H0300.02A8 | Rear: H0301.T |
| | | <i>Blast</i> Front: H0300.T | Rear: H0301.T |
| | Battery # | <i>ALL</i> 65948-00 | |
| | Air cleaner # | <i>XB</i> P0213.02A8 | |
| | | <i>Blast</i> P0213.T | |
| | Spark Plug # | <i>ALL</i> 32335-04 | 10R12A |
| | Fork Oil | <i>Blast</i> 9.2 oz/272 ml | |
| | | <i>XB9R/12R</i> 4.21" | |
| | <i>XB9SX/12S/12Ss</i> 4.21" | | |
| | <i>XB12Scg</i> 4.29" | | |
| | <i>XB12X</i> 4.45" | | |



2008 TIRE CHART

| | MODEL | FRONT | REAR |
|---------|-----------------|----------|----------|
| TOURING | ALL | 36psi | 36-40psi |
| | FLHTCUSE3 | 36psi | 36-40psi |
| | FLHRSE4 | 36-38psi | 38-42psi |
| SOFTAIL | FXST/B/C | 30psi | 38-42psi |
| | FLSTF | 36psi | 38-42psi |
| | FLSTC/N | 36psi | 36-40psi |
| | FXCW/C | 30psi | 38-42psi |
| | FXSTSSE2 | 36psi | 38-42psi |
| | FXDF | 36psi | 36-40psi |
| DYNA | ALL except FXDF | 30psi | 36-40psi |
| | FXDSE2 | 30psi | 38-42psi |
| | ALL | 30psi | 36-40psi |
| XL | ALL | 30psi | 36-40psi |
| VROD | VRSCD | 36psi | 38-40psi |
| | VRSCDX/AW | 36psi | 38-42psi |
| BUELL | All XB Models | 34 psi | 36 psi |
| | Blast | 34 psi | 36 psi |
| | AT GVWR | 32psi | 36psi |